

# **38-200** SERIES

# ATMOSPHERIC TYPE VACUUM BREAKER

Job Name:	Contractor:
Job Location:	P.O. Number:
Engineer:	Representative:
Tag:	Wholesale Distributor:

#### **SPECIFICATIONS**

The  $\frac{1}{4}$ "  $-\frac{3}{4}$ " Atmospheric Type Vacuum Breakers shall be Apollo<sup>®</sup> 38-200 Series. The device is designed to prevent contamination of potable water due to back-siphonage. The 38-200 Series is not designed for backpressure conditions or continuous pressure applications longer than 12 hours in a 24-hour period and should only be installed in areas where spillage of water could not cause damage.

#### **FEATURES**

- Compact and easy to maintain
- · Suitable for hot or cold water service
- · Corrosion-resistant forged brass body
- MADE IN THE USA

# **MATERIAL SPECIFICATIONS**

Part Name	Material
Body	Forged Brass
Seat Disc	Silicone
Float	Polypropylene
Cap and Guide	Noryl <sup>®</sup>
Canopy	Chrome-plated Steel
Screw	Zinc-plated Steel

# ORDERING INFORMATION

38 - 2 X X - 0 X

BODY STYLE	
SIZE <sup>*</sup>	
FINISH	

#### **BODY STYLE**

- **□ 0** Normal (90° Flow)
- ☐ 3 Deck Mounted ("U" Flow)

#### SIZE

1 - 1/4"	□ 2 - %"
<b>3</b> – ½"	□ 4 - ¾"

\*Note: Deck-mounted available sizes are 1/4" & 3/6" only

#### **FINISH**

- ☐ 1 Rough Brass
- □ 3 Rough Chrome
- ☐ 6 Polished Chrome

#### **APPROVALS**

ASSE® 1001, ANSI® A112.1.1, CSA® B64.1.1 and IAPMO

#### **PERFORMANCE RATING**


Maximum Operating Pressure 125 psi Temperature Range up to 212 °F





## **DIMENSIONS (in.)**

Size	Α	В	С	Wt. (lb.)
1/4"	1 1/8	2 %	1	.51
3/8"	1 1/8	2 %	1	.48
1/2"	1 1/4	2 %	1 1/4	.55
3/4"	1 ½	3	1 ½	.63
* 1/4" *	3/4	2 ½	1 ½	.26
* 3/8" *	7/8	2 ½	1 3/4	.31



## **FLOW CURVES**

