



Model #	Input Supply Voltage* V	Sec KVpk	Secondary Voltage RMS	mA	Pri. A	Primary VA	Input Supply Frequency Hz	Secondary Frequency KHz	Storage Temperature °C	Operating Temperature °C	Operating Relative Humidity %	Loading Air Gap Inches
ELECTRONIC OIL IGNITORS - Mid Point Ground												
2270	12 Vdc	20	-	22	2.5	36	50/60	>18	-40 to +80	-30 to +40	90	1/16 - 3/16
2275	120	17.5	-	45	0.72	87	50/60	20	-40 to +80	-30 to +40	90	1/16 - 3/16
2280	240	17.5	-	45	0.38	87	50/60	20	-40 to +80	-30 to +40	90	1/16 - 3/16
PRODUCTION TRANSFORMERS - Mid Point Ground												
2721	120	-	10,000	23	2.08	250	60	-	-40 to +80	-30 to +40	90	1/8 - 3/16
2741	120	-	10,000	23	2.08	250	60	-	-40 to +80	-30 to +40	90	1/8 - 3/16
2729	220	-	10,000	23	1.14	250	50	-	-40 to +80	-30 to +40	90	1/8 - 3/16
2730	110	-	10,000	23	2.2	250	50	-	-40 to +80	-30 to +40	90	1/8 - 3/16
421	120	-	10,000	23	2.08	250	60	-	-40 to +80	-30 to +40	90	1/8 - 3/16
2744	240	-	10,000	23	1.04	250	60	-	-40 to +80	-30 to +40	90	1/8 - 3/16
444	240	-	10,000	23	1.04	250	60	-	-40 to +80	-30 to +40	90	1/8 - 3/16
911	240	-	10,000	23	1.04	250	50	-	-40 to +80	-30 to +40	90	1/8 - 3/16
912	120	-	10,000	23	2.08	250	50	-	-40 to +80	-30 to +40	90	1/8 - 3/16
2714	120	-	12,000	20	2.29	275	60	-	-40 to +80	-30 to +40	90	1/8 - 3/16
2742	220	-	12,000	20	1.14	250	50	-	-40 to +80	-30 to +40	90	1/8 - 3/16
INDUSTRIAL GAS TRANSFORMERS - One End Ground												
1092	120	-	6,000	25/20	2.08	250/180	50/60	-	-40 to +80	-30 to +40	90	1/16 - 1/8
1112	240	-	6,000	20	0.75	180	60	-	-40 to +80	-30 to +40	90	1/16 - 1/8
1196	240	-	6,000	20	0.75	180	50	-	-40 to +80	-30 to +40	90	1/16 - 1/8
542	120	-	10,000	23	2.2	265	60	-	-40 to +80	-30 to +40	90	1/16 - 1/8
INDUSTRIAL GAS IGNITORS - Single Pole, One End Grounded												
2260-TP	120	15.6	-	28	0.6	72	50/60	>20	-40 to +80	-30 to +40	90	1/16 - 1/8
2260-TW	120	15.6	-	28	0.6	72	50/60	>20	-40 to +80	-30 to +40	90	1/16 - 1/8
2260-P	120	15.6	-	28	0.6	72	50/60	>20	-40 to +80	-30 to +40	90	1/16 - 1/8
2260-TWG	120	15.6	-	28	0.6	72	50/60	>20	-40 to +80	-30 to +40	90	1/16 - 1/8
2265-TP	230	15.6	-	30	0.3	72	50/60	>20	-40 to +80	-30 to +40	90	1/16 - 1/8
2265-TW	230	15.6	-	30	0.3	72	50/60	>20	-40 to +80	-30 to +40	90	1/16 - 1/8
2265-P	230	15.6	-	30	0.3	72	50/60	>20	-40 to +80	-30 to +40	90	1/16 - 1/8
2265-TWG	230	15.6	-	30	0.3	72	50/60	>20	-40 to +80	-30 to +40	90	1/16 - 1/8

*Input Supply Voltage (V) must be within 10% tolerance.

Technical and Electrical Specifications