

# XVERS®

(POWERED BY KÖR™)

More heat in less space.

1 MMBTUH – 4 MMBTUH

**H** 94.5-95.7% Efficiency



Click icon or view standalone page to learn more.



## Maximum Performance

- 316L stainless steel KÖR heat exchanger for high-efficiency heating and maximum corrosion resistance (patent pending)
- Integrated flow meter for continuous monitoring and optimization with the Dynamic Protection controls algorithm
- Engineered for reliable indoor/outdoor performance and more uptime
- HO<sub>2</sub>T Track and Trim continuously monitors and controls the oxygen concentrations in boiler flue gas and automatically adjusts for fuel and airflow to maintain optimum combustion



Applicable for hydronic heating in hospitals, schools, multi-family housing, and more.



## Installation Versatility

- 4 Thru The Door: the only 4 MMBTUH condensing boiler on the market that fits through the door with ease for convenient installation
- Forklift and pallet jack accessible base for easy transportation
- Multiple vent material options: PVC, CPVC, polypropylene, or stainless steel
- High elevation models available up to 10,000 ft.
- Conforms to Buy American Act



## Easy to Service

- Improved cabinet design with multiple smaller, lighter, easier-to-handle jacket panels for convenient access to key components
- Ultra-short height provides the best top access for servicing in compact boiler rooms
- Simple gas train design: a turnkey solution for easy commissioning and servicing



## Intelligent Controls

- VERSA IC controls with LCD touchscreen display
- Raymote access
- Control the uncontrolled with Dynamic Protection for more uptime and longer life

## Optional Features

- |  |  |
|--|--|
| <input checked="" type="checkbox"/> Variable or fixed speed pump | <input checked="" type="checkbox"/> HO <sub>2</sub> T Track & HO <sub>2</sub> T Track and Trim |
| <input checked="" type="checkbox"/> Motorized isolation valve    | <input checked="" type="checkbox"/> CSD-1 package  |
| <input checked="" type="checkbox"/> BACnet gateway               | <input checked="" type="checkbox"/> High elevation models                                      |
| <input checked="" type="checkbox"/> Condensate treatment kit     | <input checked="" type="checkbox"/> Standard Stock Products                                    |



HIGH EFFICIENCY



Learn more about  
**XVers + KÖR boilers**  
at [Raypak.com](http://Raypak.com)

Model	MBTU/h (kW)		Minimum BTU/h (kW) Input	Turn Down	AHRI Thermal / Combustion Efficiency (%)	Dimensions - Inches (mm)						
	Input	Output				B Width	C Base Depth	D Overall Depth	G NPT	K Flue Ø	N C/A Ø	P
1007	999 (293.1)	952 (279.0)	100,000 (29.3)	10:1	95.3 / 95.5	24 (610)	44 (1118)	56.3 (1430)	1-1/4 (31.75)	6 (152)	6 (152)	71.6 (1818)
1257	1,250 (366.3)	1,196 (350.5)	104,000 (30.5)	12:1	95.7 / 96.0	26 (660)	48 (1219)	60.3 (1531)		8 (203)	8 (203)	
1507	1,500 (439.6)	1,427 (418.2)	100,000 (29.3)	15:1	95.1 / 95.3	26 (660)	48 (1219)	60.3 (1531)		8 (203)	8 (203)	
2007	1,999 (586.0)	1,903 (557.8)	200,000 (58.6)	10:1	95.2 / 95.4	30 (762)	53 (1346)	65.3 (1659)		8 (203)	8 (203)	
2507	2,499 (732.3)	2,374 (695.7)	300,000 (88.0)	8:1	95.0 / 96.2	34 (864)	58 (1473)	70.3 (1786)	2.0 (51.0)	10 (254)	10 (254)	74.6 (1894)
3007	3,000 (879.2)	2,862 (838.7)	300,000 (88.0)	10:1	95.0 / 95.4	34 (864)	58 (1473)	70.3 (1786)		10 (254)	10 (254)	
3507	3,500 (1025.7)	3,329 (975.6)	400,000 (117.2)	9:1	95.0 / 95.1	34 (864)	58 (1473)	70.4 (1788)		12 (305)	12 (305)	
4007	4,000 (1172.3)	3,788 (1110.1)	400,000 (117.2)	10:1	94.5 / 94.7	34 (864)	58 (1473)	70.4 (1788)		12 (305)	12 (305)	

